



use 5/16-18 or 8mm bolts for mounting.

case drain port: #4 GAS thread for NPT or BSPP

$\phi$ .375 OD x .035 wall feed tube, 304 SS  
[9.53]

hydraulic ports: #8SAE Both sides. birotational motor

2.942  
[74.72]

3/8"-16 thread w/locknut

5.000  
[127]

3.500  
[88.90]

9.491  
[241.07]

7.000  
[177.80]

5.998  
[152.34]

$\phi$ .375 THRU 4X  
[9.53]  
mount holes

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF <INSERT COMPANY NAME HERE>. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF <INSERT COMPANY NAME HERE> IS PROHIBITED.

		UNLESS OTHERWISE SPECIFIED:	NAME	DATE	Ledebuhr industries, Inc.	
		DIMENSIONS ARE IN INCHES	DRAWN		TITLE:	
		TOLERANCES:	CHECKED		PT099-25-0200 and	
		FRACTIONAL $\pm$	ENG APPR.		PT049-25-0200	
		ANGULAR: MACH $\pm$ BEND $\pm$	MFG APPR.		SIZE	DWG. NO.
		TWO PLACE DECIMAL $\pm$	Q.A.		<b>A</b>	PT099-25-0200
		THREE PLACE DECIMAL $\pm$	COMMENTS:		REV	
		INTERPRET GEOMETRIC TOLERANCING PER:			SCALE: 1:3	WEIGHT:
		MATERIAL				SHEET 1 OF 1
		FINISH				
NEXT ASSY	USED ON	APPLICATION	DO NOT SCALE DRAWING			

5

4

3

2

1